


CAMERA

TD-9524S3L

2MP IR Water-proof Turret Network Camera



- 2MP (1920 × 1080) H.265 coding
- Max.resolution: 1920 × 1080
- ICR auto switch, true day / night, ROI coding
- 3D DNR, digital WDR, HLC, BLC, defog
- 10~20m IR night view distance
- PoE power supply (optional)
- 1CH built-in MIC
- P2P function optional
- IP 67 ingress protection
- Support dual streams
- Support mobile surveillance by smart phones with iOS and Android OS
- Intelligent analytics: video blur detection, line crossing detection and region intrusion detection



en.tvt.net.cn

For more information, please visit our website

Shenzhen TVT DIGITAL TECHNOLOGY CO., LTD.

Address: 23rd Floor, Block B4, Building NO.9, Shenzhen Bay Eco-Technology Park, Nanshan District, Shenzhen, Guangdong Province, P.R.China

Tel: +86-755-36995888

Web site: <http://en.tvt.net.cn>

Fax: +86-755-33104777


E-mail: overseas@tvt.net.cn

SPECIFICATIONS

Specifications	Model	TD-9524S3L
Camera		
Image Sensor		1 / 3.2 "CMOS
Image Size		1920×1080
Electronic Shutter		1 / 25 s ~ 1 / 100000 s
Iris Type		Fixed Iris
Min. Illumination		0.012lux @F1.2, AGC ON; 0 lux with IR 0.046 lux @ F2.0, AGC ON; 0 lux with IR
Lens		2.8 mm @F2.0, (fixed lens), horizontal field of view: 93.7° 3.6 mm @F2.0, (fixed lens), horizontal field of view: 75.8°
Lens Mount		M12
Wide Dynamic Range		Digital WDR
BLC		Yes
HLC		Yes
Defog		Yes
Digital NR		3D DNR
Angle Adjustment		Pan: 0°~360°; Tilt:0°~75°; Rotation: 0°~360°
Image		
Video Compression		Main stream: H.265 / H.264; Sub stream: H.265 / H.264 / MJPEG
H.265 Compression Standard		Main Profile@Leve4.1 High Tier
Resolution		1080P (1920 × 1080), 720P (1280 × 720), D1, 480 × 240, CIF
Main Stream		60Hz : 1080P/720P(1~30fps); 50Hz : 1080P/720P(1~25fps)
Sub Stream		60Hz : D1/CIF/480×240(1~30fps); 50Hz: D1/CIF/480×240 (1~25fps)
Bit Rate		64 Kbps ~ 6 Mbps
Bit Rate Type		VBR / CBR
Image Settings		ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
ROI		Each ROI to be configured separately
Audio Compression		G711A/U
Interfaces		
Network		RJ 45
Video Output		No
Audio		1CH built-in MIC
Storage		No
Hardware Reset		No
Functions		
Remote Monitoring		Web browsing, CMS remote control
Online Connection		Support simultaneous monitoring for up to 3 users; Support multi-stream real time transmission
Network Protocol		UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Interface Protocol		ONVIF
Storage		Network remote storage
Smart Alarm		Motion detection
Intelligent Analytics		Region intrusion detection, video blur detection and line crossing detection
General Function		Watermark, IP address filtering, video mask, heartbeat, illegal login lock
PoE		Optional
IR Distance		10 ~ 20m
Ingress Protection		IP 67

Others	
Power Supply	DC12V(PoE power supply optional)
Power Consumption	< 5 W
Operating Environment	- 20 °C ~ 55 °C (-4°F~131°F) Humidity: less than 95 % (non-condensing)
Dimensions (mm)	Φ 94.8 × 82.8
Weight (net)	Approx. 0.287KG
Installation	Ceiling mounting (Wall mounting available with the junction box and bracket)
Certificate	CE, FCC
Environmental Protection	Complies with Directive EU RoHS, WEEE(2012/19/EU) , directive 94/62/EC and REACH(EC1907/2006)

DIMENSIONS



AVAILABLE ACCESSORIES



AVAILABLE MODEL

Available Model	TD-9524S3L(D/PE/AR1)
	TD-9524S3L(D/AR1)