

Conference microphone Delegate Unit

TF-0301WA



Features

- 1. The representative machine has the function of applying to speak, and the chairman can approve the applicant to speak.
- 2. Supports switching between four language interfaces: Chinese, English, Russian and French.
- 3. Supports clock display function, which can display date and time: year, month, day, hour and minute.
- 4. It has a custom voting function, which is flexible and convenient.
- 5. With voice control function, you can adjust the voice control sensitivity, intelligently turn on the microphone and set the closing time.
- 6. It has speech timing and scheduled speech functions.
- 7. It has a 5-band EQ adjustment function (adjustable by entering the password in the PC software), which can adjust different sound effects according to the speaker's voice characteristics until the perfect effect is achieved.
- 8. It has a 4.3-inch color screen that can display information such as microphone on/off, ID settings, battery level, signal strength, etc.; it supports multitouch capacitive buttons.
- 9. It has a USB charging port and supports 18W fast charging.
- The microphone uses a 48kHz sampling rate, which is higher than the sound quality of CD, clear and bright. It has DSP audio processing inside, no "puff" low-frequency impact sound; it has feedback suppression function inside, which can effectively prevent howling.
- It uses 128-bit AES encryption technology and supports WPA/WPA2 wireless security technology to prevent eavesdropping and unauthorized access, providing higher confidentiality of the conference system.
- 12. It comes standard with 6 large-capacity lithium batteries with a battery capacity of up to 14400mA/h, which can provide continuous speaking for 17 hours or continuous working for 24 hours.
- It has a 3.5mm headphone jack and supports connecting an external microphone .
- It has a 5-band EQ adjustment function (adjustable by entering the password in the PC software), which can adjust different sound effects according to the speaker's voice characteristics.



Specification

Display	4.3-inch color screen
Dimensions (LxWxH)	196x134x63 mm
Installation	Desktop
Microphone Type	Cardioid electret
Frequency Response	8 0Hz~1 6k Hz
Sensitivity	- 41 ±1.5dB (0dB=1V/Pa,at 1KHz)
Maximum SPL	100dB
Signal-to-Noise Ratio	>80dB(A)
Crosstalk	>70dB
Dynamic Range	>80dB
THD	<0.1%
Maximum power consumption	3 W
Power supply	Battery powered
color	grey
Voting function	Five-key election, three-key voting, custom voting
Sign-in function	Sign in by key
Standby mode working time	24 hours
Working time in speech mode	17 hours
Mixed mode working time	17 hours
Wireless frequency range	5GHz
Battery capacity	14400mAh
weight	About 0.7 kg
Mic rod length	409mm